

SEGURA

600L/H 175BAR



TIPO / TYPE



EQUIPAMIENTO / FEATURES



DOTACIÓN / INCLUDED



EMBALAJE / PACKAGING



RECAMBIOS FRECUENTES / FREQUENT SPARE PARTS



MODELO / MODEL

Tipo/ Type

Bomba / Pump

Presión máxima / Maximum pressure

Caudal máximo / Maximum flow

Dotación / Included

Modelo motor / Engine model

Cilindrada / Displacement

Tipo de motor / Engine type

Nivel sonoro a 7mts / Sound level to 7m

Tipo de arranque / Startup type

Capacidad depósito combustible / Fuel tank capacity

Consumo combustible - Autonomía (promedio) / Hourly consumption - Autonomy (average)

Capacidad de aceite motor - Tipo de aceite / Oil capacity engine - Oil type

Capacidad de aceite bomba - Tipo de aceite / Oil pump capacity - Oil type

Kit de transporte / Transportation kit

Dimensiones L x A x Alto (cm) / Dimensions L x W x H (cm)

Peso máquina / bruto embalaje (Kg) / Machine weight / gross packaging (Kg)

Referencia / Reference

SEGURA

Bomba TRIPLEX con transmisión directa a motor térmico
TRIPLEX pump direct driving by combustion engine

ANNOVI REVERBERI RSV2.5G25D-F25

175BAR

600L/H

Manguera 15mts, Lanza alta presión, boquillas 0°-15°- 40°- Jabón
Hose 15mts, spray gum, nozzle kit 0°-15°-40°-Soap
GENERGY SG70

210cc

Gasolina, 4 tiempos OHV refrigeración forzada por aire
Gasoline, 4-stroke OHV, air forced cooling
73dB (A)

Manual / Recoil

3.6L

1.2 l/h - 3h

0.6L SAE10W30 - SAE10W40

0.4L SAE15W40

Si, con neumáticos de goma 13" y llanta metálica
Yes, with 13" rubber tires and metal rim

64 x 53x 80

47

2013060